

QUEENSLAND

IRRIGATION AND WATER SUPPLY COMMISSION



REPORT ON

GROUNDWATER INVESTIGATIONS

HAUGHTON RIVER

1967

## TABLE OF CONTENTS

Page No.

### SUMMARY

PURPOSE	1
ORIGIN	1
NATURE AND EXTENT OF DEVELOPMENT	1
NATURE OF INVESTIGATIONS	1
CONCLUSIONS FROM INVESTIGATIONS	2
Location and Adequacy of Available Supplies	2
Possibility of Supplies from Deeper Aquifers	3
Groundwater Supplies outside Present Development	3
FURTHER INVESTIGATION OF IMPROVEMENT TO SUPPLY	3
PROTECTION OF EXISTING SUPPLY	4

### DESCRIPTION OF AREA

LOCATION	4
CLIMATE AND RAINFALL	4
HAUGHTON RIVER FLOWS	5
INDUSTRY	5

### INVESTIGATIONS

AIMS	6
METHODS	7
GEOLOGY AND GEOMORPHOLOGY	8
GEOPHYSICAL INVESTIGATIONS	8
Results of Geophysical Surveys	9
WATER LEVELS	9
WATER QUALITY	10
Recent Alluvials	10
Older Alluvials	12
NATURAL REPLENISHMENT	13
SALINE WATER INTRUSION	14
SAFE YIELD	14
DEFICIENCY IN SUPPLY FROM AQUIFER	16
EXTENT OF SHORTAGE OF SUPPLY	16
POSSIBLE METHODS OF IMPROVEMENT TO SUPPLY	17
Prevention of Sea Water Intrusion	17
Provision of Additional Supply	17
PROTECTION OF EXISTING SUPPLY	18

### LIST OF TABLES

Table I	Temperature and Relative Humidity in Townsville - Bowen Region	4
II	Water Quality Analyses by Sugar Experimental Stations	11
III	Saline Waters in Older Cainozoic Alluvials	12
IV	Storage Coefficient and Transmissibility	15

LIST OF APPENDICES

- Appendix A - Geology and Geomorphology  
Appendix B - Water Quality  
Appendix C - Number of Days of No Flow - Haughton River 14.5 Miles

LIST OF FIGURES

Figure No.

- |    |   |
|----|---|
| 1  | General Plan and Geology and Bedrock Contours |
| 2  | Giru and Ayr Rainfall                         |
| 3  | Developed Area - Geology and Water Quality    |
| 4  | Developed Area - Irrigated Areas              |
| 5  | Investigation Bores and Bore Lines            |
| 6  | Cunningham Line 1" = 80 chains                |
| 7  | Townsville Road Line 1" = 80 chains           |
| 8  | Camerons Line 1" = 20 chains                  |
| 9  | Cunningham Line (Haughton Section)            |
| 10 | The Dam Line                                  |
| 11 | Poletti Line                                  |
| 12 | Shirbourne Line                               |
| 13 | Townsville Road Line (Haughton Section)       |
| 14 | Old Road Line                                 |
| 15 | Ironbark Line                                 |
| 16 | Woodstock Road Line                           |
| 17 | Anabranh Line                                 |
| 18 | Townsville Road Line (Anabranh)               |

## SUMMARY

### PURPOSE:

The purpose of this report is to present information available to date from an investigation in respect of the sugar cane producing area astride of and adjacent to the Haughton River around the Town of Giru dealing with -

- (a) The location and adequacy of existing underground resources at Giru to meet present irrigation requirements.
- (b) The possibility of obtaining additional supplies from deeper aquifers in the areas of existing development.
- (c) The possibility of obtaining underground supplies in the Region from the Haughton River to Barratta Creeks.

The report also sets out further desirable investigations of possible additional supply for the present area of development; and action considered desirable to safeguard and equitably distribute available supplies.

### ORIGIN:

The investigations began in 1964 following concern expressed by the Haughton Sugar Company and the Invicta Mill Suppliers' Committee as to the adequacy of existing underground supplies to meet present and anticipated future demands.

### NATURE AND EXTENT OF DEVELOPMENT:

Irrigation in the Haughton River area around the Town of Giru is utilised virtually entirely on sugar cane production for the Haughton Sugar Milling Co. Mill at Giru.

The Mill has an allotted annual peak of 400,679 tons (1965/66). In the 1965/66 year, 193,229 tons of cane were produced from some 9,200 acres in the Giru area the balance being produced in the Burdekin Irrigation Area (Clare, Millaroo and Dalbeg).

Almost all the Giru canelands are situated either in a strip about 1 mile wide on each side of the Haughton River over a length of some eleven miles or a further strip some four miles long along Healey's Lagoon which approximately follows a former Anabranche of the River (see Figure 4).

Average annual rainfall at Giru (see Figure 2) is 50.4 inches as compared with 42.4 inches at Ayr thus indicating the necessity for irrigation for satisfactory sugar cane production.

### NATURE OF INVESTIGATIONS:

The investigations have included geophysical surveys by the Bureau of Mineral Resources; geological reconnaissance and mapping; investigation drilling strata logging and pump testing; collection of information on private bores and use of water from these facilities; studies of water quality; and assessment of supply available from the present sources.

## CONCLUSIONS FROM INVESTIGATIONS:

### Location and Adequacy of Available Supplies:

#### (a) Location -

Generally as shown in Figure 3 the lands in the Giru area are older Cainozoic alluvials deposited originally by the Haughton River. More recently the River has cut a trench some 30 feet deep through these older alluvials and redeposited more recent (Quaternary) alluvials in this trench.

This area of more recent alluvials (see Figure 3) is in three main sections:

- (i) along the river itself where they occupy a relatively narrow strip in the upstream section, broaden in a minor delta around the Town of Giru and then become a relatively narrow strip again about 1 mile downstream of the railway line;
- (ii) the Anabran section which is located in an old Anabran of the River which leaves the River section a short distance downstream of the Ironbark Creek effluent and the remains of which form Healey's Lagoon;
- (iii) the Hodel section which leaves the river section approximately one mile upstream of the railway line and crosses the line in the vicinity of the Hodel siding.

Adequate rates of supply of groundwater for irrigation can be obtained only from these recent alluvials which thus provide a rather unique limited and fairly well defined aquifer.

Although there is water in the older alluvials the quantities that can be extracted are small and the quality is poor.

#### (b) Storage in and Replenishment of Aquifer -

From the investigations it is estimated that at the fully recharged stage the volume of water stored in the aquifer which is available for extraction is some 10,000 acre feet. This is sufficient to meet full irrigation requirements of 9,200 acres for some 160 days. Replenishment of the aquifer comes virtually entirely from flow in the Haughton River although some additional contribution is derived from runoff from Mt. Elliot to the Anabran section in the vicinity of Healey's Lagoon.

No-flow periods in the river between 1952 and 1967 have exceeded 160 days on eight occasions with a maximum for 1966/67 of 345 days. Occurrence of such periods between 1900 and 1952 are estimated to be more frequent than 1952 to 1967.

#### (c) Quality -

The base of the aquifer is below sea level to upstream of Ironbark Creek offtake, i. e. above the extent of present irrigation use.

Because of this, once river flow ceases and water levels in the aquifer are drawn down by pumping, quality of the groundwater deteriorates due principally to the intrusion of sea water.

## (d) Adequacy of Supply -

If sea water intrusion could be prevented to allow full drawdown of the aquifer storage the supply available from the aquifer would be insufficient to meet requirements for full irrigation of the existing area on an average of at least 50 percent of years.

An additional supply of some 10,000 acre feet is estimated to be necessary to provide full irrigation requirements. This supply can only be provided by surface water storage.

To make any additional supply effective also requires measures to include sea water intrusion to reduce quality deterioration.

Possibility of Supplies from Deeper Aquifers:

The investigation has shown that there are no deeper aquifers of satisfactory quality water in the existing area of development.

Drilling below the base of the aquifer should be prohibited as it could facilitate sea water intrusion.

Groundwater Supplies Outside Present Development:

It has been firmly established that there are no deeper aquifers of suitable quality water outside the area of present development beneath uncultivated lands between the Haughton River and Healey's Lagoon.

It has also been established that except for some localised areas there is little prospect of further development of satisfactory groundwater supplies between the Haughton River and Barratta Creeks.

FURTHER INVESTIGATION OF IMPROVEMENT TO SUPPLY:

The following further investigations of possible improvement to the groundwater supplies are considered desirable:

- (a) The possibility of sea water barriers across the aquifer in the Haughton River section about  $1\frac{1}{2}$  miles downstream of the Railway Bridge; the Anabran section a short distance upstream of the Bruce Highway and on the Hodel section in the vicinity of the Railway.
- (b) The possibility of construction of surface storages to provide some 10,000 acre feet of additional supply -
  - (i) on the Haughton River in conjunction with a possible sea water barrier about  $1\frac{1}{2}$  miles downstream of the Railway;
  - (ii) on the Haughton River about 1 mile above the Bruce Highway;
  - (iii) further upstream on the Haughton River;
  - (iv) on the lower end of Healey's Lagoon.

PROTECTION OF EXISTING SUPPLY:

In order to safeguard existing landholders by protecting the existing supply against further and unequitable over exploitation, facilitating sea water intrusion by drilling below the bed of the aquifer and sharing available supplies as equitably as practicable, it is also considered desirable to declare the area one of "Sub Artesian Supply" under the provisions of The Water Acts.

This will enable the licensing of existing and new bores and placing conditions on drilling and use of bores, as set out in detail in the report, to achieve the above objectives.

DESCRIPTION OF THE AREALOCATION:

Centre of operations and focal point of the sugar producing area is the Haughton Sugar Company's Invicta Mill which is situated at the Township of Giru, on the Haughton River, some 30 miles south of Townsville on the North Coast Railway. The Bruce Highway from Cairns to Brisbane by-passes Giru by some two miles. The Haughton River discharges into Bowling Green Bay between Cape Cleveland and Cape Bowling Green and Giru Township is on the left bank of the river some ten miles from its mouth. The area surrounding Giru Township has a population which varies from 800 in the off season to 1,000 in the crushing season.

CLIMATE AND RAINFALL:

The climate of the area is warm and sub-humid with the maximum rainfall in summer. There are two main seasons, a hot wet summer period of variable duration and intensity and a warm dry winter period. Seasonal changes are slow and are associated with a regular annual temperature movement. Temperatures are moderate to high throughout the year.

TABLE ITEMPERATURE AND RELATIVE HUMIDITY IN  
TOWNSVILLE - BOWEN REGION

Summer Months			Winter Months		
Maxima °F	Minima °F	Relative Humidity	Maxima °F	Minima °F	Relative Humidity
85 - 90	70 - 75	70%	75 - 80	55 - 60	60%

Rain falls mostly between October and April with the greatest concentration between January and March. The intensity of rainfall in the summer months is high and the average fall per wet day for the Townsville-Bowen region is of the order of 70 points. During the summer months the intensity often exceeds 100 points per wet day.

Actual annual rainfall records at Giru and Ayr are shown in Figure 2 for 1882 to 1966 together with three and five year moving averages. For Giru records are not available prior to 1933. For the period 1882 to 1932 the values shown have been estimated from the records for Ayr.

For the years of record the average annual rainfall at Giru is 50.4 inches and 42.4 inches at Ayr.

The three years 1964 to 1966 have all been below average at Giru and the area has consequently been subject to drought. As shown in Figure 2 this is not an unusual occurrence as there appears to have been five other periods of three or more successive years when estimated or recorded rainfall was below average. Of these there was one of four, one of six and one of eleven successive years of below average rainfall.

#### HAUGHTON RIVER FLOWS:

River height records for the Haughton River are available since 1952 from a gauge at 14.5 miles on the River near the old Townsville road crossing. These show that although the river flows each year there are no long periods of no flow.

Details of the number of days in each month when no flow was recorded are shown in Appendix C.

These show the following substantial continuous periods of no flow:

August, 1952 - January, 1953	173 days
June, 1953 - January, 1954	225 days
October, 1956 - January, 1957	108 days
April, 1957 - February, 1958	320 days
September, 1958 - January, 1959	150 days
August, 1959 - December, 1959	139 days
July, 1960 - January, 1961	233 days
April, 1961 - January, 1962	283 days
July, 1962 - January, 1963	197 days
July, 1963 - January, 1964	123 days
August, 1964 - December, 1964	127 days
July, 1965 - January, 1966	168 days
March, 1966 - March, 1967	346 days

#### INDUSTRY:

Apart from minor beef cattle assignments, sugar cane production is the sole crop and industry of the Giru-Haughton River area. Sugar cane growing began in 1905 and cane first went to Pioneer Mill until crushing began at Invicta Mill in 1920. Until recently cane for Invicta Mill came by rail from Ingham as well as from the area around Giru. This cane from Ingham now goes to Victoria Mill and has been replaced by cane which is transported some twenty-four miles by tramline from the Burdekin Irrigation Areas of Claredale, Millaroo and Dalbeg. However, the area of 9,200 acres in the Giru area is still more than half the total assignment of 17,000 acres for Invicta Mill.



As shown in Figure 4, the main cultivation occurs in two strips each approximately one mile in width. The major strip occupies land on both banks of the Haughton River from half mile downstream of the railway line at Giru to ten miles upstream. The minor strip of four miles length is bounded by Healey's Lagoon which marks the location of a former Anabranche of the Haughton River.

As can be seen from this description, cultivation of the area was first centred about two sources of surface water, namely the Haughton River and Healey's Lagoon. With increased assignment and production, supplies of water have been progressively augmented by underground supplies from spears in the Haughton River and from its former anabranche. In addition consideration, time and money has been expended by private landholders in the search for additional underground supplies outside the known areas. Search has also been made for deeper supplies in the bed of the Haughton River. All these searches have been unsuccessful and support the results obtained by the Commission's investigation.

Sugar cane production at Giru has the reputation of being carried out mainly by dry farming methods with irregular assistance from irrigation sources. This is probably fallacious and is probably based on the memory of the years of higher rainfall from 1948-1958. As can be seen from Figure 2, the average rainfall at Giru is not dramatically higher than that at Ayr where irrigation is consistently practised. Undoubtedly the backdrop of Mt. Elliot aids the local rainfall but not to the extent claimed. With the present more normal rainfall pattern, irrigation is essential if the local sugar cane industry is to prosper.

### INVESTIGATIONS

#### AIMS:

The investigations were initiated in 1964 following urgent requests from the Haughton Sugar Company, the owners of the Invicta Mill and Invicta Mill Suppliers' Committee, who expressed concern at the inadequacy of supplies and quality of water available for irrigation. At the time of the first request, continued expansion and granting of further assignments were still envisaged.

After consultation, the Sugar Company, Suppliers' Committee and the Irrigation Commission decided on four initial objectives:

- (a) Search for deeper aquifers of suitable quality water in the areas of the present existing irrigation facilities.
- (b) Search for deeper aquifers of suitable quality water in the uncultivated area between the Haughton River and Healey's Lagoon, e. g. Portions 31 and 40, Parish of Scott.
- (c) Endeavour to locate underground supplies in areas of possible future expansion -
  - (i) along the Giru-Clare tramline in proximity to the Haughton River up to the junction of the tramline with Barratta Creeks, i. e. over the first sixteen miles from Giru;
  - (ii) Palm Creek and St. Margarets' Creek areas in the vicinity of the Townsville Road;
  - (iii) Spring Creek farming area off the Woodstock Road.

- (d) Carry out a regional search for underground supplies in the undeveloped uncultivated area between the Haughton River and the Barrattas, both for -
- (i) future long term development of this area;
  - (ii) better understanding of the factors controlling underground supplies.

During the course of the investigation, these objectives were modified to include:

- (e) The determination of aquifer characteristics.
- (f) Preliminary assessment of the possibilities of artificial replenishment.

However, because of the general nature of the investigation, only a very preliminary assessment has been made of (e) and (f).

#### METHODS:

Details of the results achieved in different phases are given under separate headings in this report. The methods used fall into the following categories or phases:

1. Geophysical surveys from June to October, 1964, by Geophysicists from the Bureau of Mineral Resources. This was separately reported on by the Bureau.
2. Percussion drilling by private contractor. This was aimed mainly at determining the availability of underground water along the Giru-Clare tramline along the Haughton River and to Barratta Creeks.
3. Percussion drilling by Commission drilling plant which was mainly concerned with aims (a), (b) and (d). This included pump tests and the calculation of storage coefficients at selected localities.
4. Geological reconnaissance mapping and strata logging of all holes drilled by Commission plant.
5. Obtaining information from individual landholders on details of bores, use of underground water and areas irrigated.

Percussion drilling by private contractor was along joint lines laid down by the Haughton Sugar Company and the Irrigation Commission. This was originally under the direction of personnel from the Haughton Sugar Company but in its later stages was supervised by the Irrigation Commission. This was mainly concerned with aim (c) (i) above and in its early stages encountered many holes with only soakage supplies. Observation pipes were not inserted as the contractor considered these to be dry holes. Under Commission supervision observation pipes were left in all holes in the later stages. However, due to the lack of near surface water bearing sands and the difficulty in distinguishing between sand and weathered older rocks, these pipes are frequently set too deep.

Percussion drilling by the Commission included placing of observation pipes in all holes and pump tests of any worthwhile supplies. In these pump tests, observations of standing water level behaviour were also made in a second bore hole in order to determine transmissibility and storage coefficients. This coefficient is derived by mathematical calculation from the observations made during the pump tests and is an important property of the aquifer which gives a relationship between the volume of stored water and the volume of saturated material.

In this investigation only a limited number of such determinations was made because very few worthwhile supplies were encountered outside the limited area of recent alluvia. No determinations were made in the bed of the Haughton River and only two determinations were made in the Anabran area. This was because the investigation was mainly concerned with areas outside the known aquifers.

The information known by the landholders about private irrigation facilities was also collected. This greatly augmented and broadened the information obtained by the investigation drilling. The information was particularly useful in its detailed confirmation of the geological interpretation and in the information obtained about aquifer thickness and standing water level.

#### GEOLOGY AND GEOMORPHOLOGY:

The general geology of the area is shown on the General Plan, Figure 1, whilst Appendix A contains notes on the geology and geomorphology of the area.

Mt. Elliot (4,000 feet) and Saddle Mountain (2,500 feet) which are formed of felspathic acidic granites rise abruptly from the coastal plain. Apart from the Cainozoic sediments in the area, these are the youngest rocks and are believed to be Permian to Mesozoic in age.

The oldest rocks in the area are the lavas, tuffs and other minor volcanics which outcrop as low rounded foothills.

The older Cainozoic alluvials cover most of the area from the foothills of Mt. Elliot across the Haughton River to the Burdekin Delta. These alluvials are generally silt, sandy clays and gravels, clays and conglomerate rocks, which do not yield water readily. Water in them is generally of very poor quality.

The Haughton River has cut a path some 30 feet deep through the Cainozoic sediments redepositing it in its own bed. These more recent alluvials contain substantial strata of sands and some gravels which are the only materials in the area from which adequate supplies of satisfactory quality water for irrigation can be obtained. It is from these deposits that virtually all present irrigation supplies are obtained.

#### GEOPHYSICAL INVESTIGATIONS:

In response to a request by the Queensland Irrigation Commission, Geophysicists from the Bureau of Mineral Resources, Geology and Geophysics carried out several surveys of the area from June to October, 1963. Results of this investigation were published in 1964 as record number 1964/111 titled "Giru Underground Water Survey, Queensland 1963" (J. T. G. Andrew and M. Wainwright).

Survey methods employed included:

- (a) Seismic Refraction which measures the velocities of shock waves through different rock layers and so interprets the thickness, depth and type of strata. Fresh granite has the greatest velocity.
- (b) Resistivity which measures the different electrical resistance of water saturated strata and relates this to the water quality. Fresh water has a high resistance.
- (c) Gravity which measures the gravitational effects of different rock types, particularly of fresh bedrock and obtains an interpretation of the underlying major structural features.

The rock type with the fastest velocity is invariably the bedrock and can always be clearly identified. In their report the Bureau Geophysicists claimed that they could distinguish between the younger unconsolidated recent alluvials and the semi-consolidated to consolidated older alluvials. They also claimed that seismic velocity in the younger alluvials was related to clay content and that good aquifers were identified by a definite velocity range of 4,500 to 5,700 feet/second. Thus by combining the results of the seismic and resistivity surveys the location of good aquifers containing fresh water were claimed to be determined (i. e. velocities 4,500 to 5,700 feet/second association with high resistivities).

#### Results of Geophysical Surveys:

The bedrock levels determined by the Bureau compare quite closely with those obtained from Commission investigation drilling and reflect the same underlying strong north-easterly deepening of the base of the Cainozoic or top of the bedrock.

A comparison between the zones of fresh water in good aquifers as obtained by the Bureau and the delineation of the recent alluvial aquifer as outlined by the Commission investigation shows close agreement in the Healey's Lagoon portion of the Anabran section but very distinct variation elsewhere. This is particularly so in Portions 44 and 28, Parish of Scott, where drilling on the Ironbark Lines has identified saline water associated with older Cainozoic alluvials. Test drilling of another area in Portions 45 and 48, where the Bureau showed good water, Parish of Selkirk gave no supplies.

In an attempt to aid the geological interpretation of the sub-surface drilling, a detailed comparison was made between the seismic interpretation of strata and the strata logging in bores. No systematic or regular comparison could be achieved so that the strata determination by seismic refraction cannot be regarded as reliable.

#### WATER LEVELS:

There are no known long term measurements of water levels in the area. Enquiries have been made from long term residents and from Invicta Mill but until the last few years only spasmodic interest was displayed in water levels. The Giru area was regarded as having a history of recurring water shortage and this was considered an annual event which would be corrected with the onset of the summer rainfall season and the anticipated flow in the Haughton River.

Measurements of standing water levels have been made by Commission staff since March, 1964 and these records are of longer duration and more systematic collection than any kept by local residents. With the co-operation of local landholders, Commission staff have measured water levels in eleven private facilities strategically located in the known aquifer at Anabranche, Giru and Hodel. Regular measurement has also been made in the observation pipes left inserted in the percussion drill holes.

This information shows seasonal fluctuations in water level from the low point before the "wet season" to the high point after the river flowed. However, the information also shows that there has been a steady downward trend since the first systematic measurements in March, 1964 and that the level in March, 1967 is generally lower than at any previous time since 1964.

The investigation has shown that for much of the time over the last three years, the water level in the aquifer has been below mean sea level. This is especially so at the time of greatest irrigation demand before the relief from summer rains. The Commission record is too short to be certain of the seasonal variation (highest to lowest reading of water level) but the information so far available shows it to be as much as 20 feet. Information collected from individual landholders quoted seasonal variations as great as 35 feet. Most users from the Haughton River claimed that in February, 1967, the water level was only just above the base of the sands, i. e. there was a seasonal variation from bed level to 30-40 feet depth.

Water levels in the older Cainozoic outside the aquifer show a similar pattern to that in the aquifer but the change is not so pronounced. As far as the water level is concerned, both the older Cainozoics and the recent alluvials act as one system though the transmissibility and water quality are quite different.

#### WATER QUALITY:

The water quality from a representative number of samples both from the aquifer and outside it is shown in Figure 3. Because of the highly saline nature of some of the samples, the water quality has been shown in terms of conductivity rather than in parts per million. Conductivity can be readily measured on a resistance meter and is a convenient indication of Total Dissolved Solids. Increasing conductivity denotes increasing salinity.

The Giru-Haughton area has a reputation as an area of poor quality water. This is especially true of the Hodel area and the area downstream from the Railway Line, on the left or town side of the river. It is not true of the whole aquifer system. However, Figure 1 shows that with the general proximity to the coast and to the low lying mud flats, this is only to be expected.

#### Recent Alluvials:

Regular collection and analysis of samples from selected private irrigation facilities and from the investigation observation holes have been made by Commission staff over the last three years. In addition the records of water quality for Giru held by the Bureau of Sugar Experimental Station (Brandon) have been examined. Some of these results are tabulated in Appendix B.

Most of the analyses have been done since 1963 with an occasional analysis in 1961 or 1962. There are no earlier records available. Most of the Bureau analyses were carried out in the poorer quality areas of the aquifer for the more conscientious farmers; only an occasional analysis was made in the better quality areas.

Both the Commission analyses and the Bureau analyses show that the water quality in the aquifer is subject to the same seasonal fluctuations as the water levels and that the poor quality water recovers very quickly after a flow in the Haughton River.

Overall in the poorer quality areas there has been a slight deterioration in quality since 1964 but elsewhere in the aquifer there is no evidence that the water quality is any worse in 1967 than 1964. It is fairly true to say that what is now poor quality water has always been so but it is also probably true that in the absence of other supplies, the farmers are using more and more of this water on their land.

Analyses by the Bureau show that most of these poor quality waters have a high sodium content and high sodium absorption ratio. (Ratio of sodium to calcium and magnesium). The Bureau analysts have repeatedly warned the farmers against continued use of such water, particularly in clayey soils with poor permeability whose tilth could be seriously and permanently impaired by clogging. This then presents a real hazard to the area. A few sample analyses are listed below:

TABLE II  
WATER QUALITY ANALYSES BY SUGAR EXPERIMENTAL  
STATIONS

Location	Conductivity micromhos/cm	Sodium Absorption Ratio	Equivalent NaCl gr/gal.
<u>Parish Scott</u>			
Portion 17	884	4.5	22.7
River opp. Portion 17	1990	7.5	60.4
River opp. Portion 17	3041	8.9	104.8
Portion 12	5720	20.0	214.0
<u>Parish Abbotsford</u>			
Portion 11V	1831	6.7	41.1
Portion 11V	2074	8.2	46.9

The river is tidal to the vicinity of the railway bridge and affects the water quality in this vicinity. In recent years, a sand dam has been constructed here by Mr. R. McLennan and presumably this has assisted in maintaining better quality water though there is little evidence of this.

Older Alluvials:

Percussion drilling outside the aquifer has shown the presence of highly saline waters both in the shallow sand veneer and in the older Cainozoic. At depth the water is as saline as sea water, e. g. Townsville Road Line B2, S4 at depth 136 feet 6 inches (R. L. - 126.87).

TABLE III  
SALINE WATERS IN OLDER CAINOZOIC  
ALLUVIALS

Depth (feet)	Supply gph.	Quality	
		Conductivity micromhos/cm	Chlorides (Cl) ppm
<u>Townsville Road Line B6, S3</u>			
8	soak	21,000	8,000
23	soak	17,000	5,800
54 - 62	1,200	6,180	1,600
68 - 71	soak	7,300	2,200
77 - 82	soak	11,500	3,800
<u>Townsville Road Line B5, S5</u>			
15	soak	saline	
38	soak	saline	
53 - 56	soak	saline	
70 - 87	soak	brackish	
87 - 95	good	28,600	
<u>Townsville Road Line B7, S6</u>			
14	soak		
25	soak	saline	
47	soak	brackish	
75 - 96	200	saline	
<u>Townsville Road Line B8, S10</u>			
21	soak	9,700	3,500
82	soak	9,500	3,540
<u>Ironbark Line B3, S5</u>			
40	soak	3,500	1,140
<u>Ironbark Line B4, S6</u>			
52	soak	4,850	1,120

From the present topography it is obvious that much of the uncultivated area between the Haughton and its former Anabranh was tidal until very recently and mangrove mud has been logged from 8 feet - 15 feet depth in holes B6, S3 and B5 S5 on the Townsville Road Line. Therefore, many of the shallow saline soaks are probably due in part to residual salts and the proximity of the nearby coastal mud flats would also make conditions more saline. However, the very saline waters at depth are almost certainly due to sea water intrusion and thus represent a considerable threat to the area.

#### NATURAL REPLENISHMENT:

The principal source for natural replenishment is runoff in the Haughton River itself. This replenishment affects both the recent aquifer alluvials and the older Cainozoic alluvials but affects the aquifer to a much more marked degree. Rapid rises in water levels have been observed in the Anabranh and Giru Delta areas following flow in the river.

In the Anabranh-Healey's Lagoon area a contributory source of replenishment of some significance is undoubtedly due to runoff from the rainfall on Mt. Elliot. Because of its topographic position, plus the presence of outcropping impermeable granite and the poor permeability of the top of the older Cainozoic, runoff from Mt. Elliot would follow a path beneath the soil to the Anabranh aquifer and Healey's Lagoon. Evidence for this localised replenishment is shown by the more pronounced upswing in water levels in February-March, 1967 for Townsville Road Line B1, S2. Vagaries in storm rainfall in February-March had been responsible for heavier falls on the north face of Mt. Elliot and had filled that part of Healey's Lagoon in Portion 55, Parish of Scott.

There is no evidence of replenishment or withdrawal between Healey's Lagoon and the aquifer but it seems feasible that in places there is movement between the two, though the banks and bed of the lagoon appear of clay composition.

Comparison between standing water levels in the older alluvials and the aquifer show a definite cone of depression on each section. This is only to be expected but results in a definite head advantage to the older alluvials. Because of their clayey composition with resulting poor storage and transmissibility, movement of water through the older alluvials is undoubtedly slow and of low yield. However, the alluvials do contain water and therefore present a source of replenishment for the aquifer. No doubt this water has helped in the past to sustain yield from the aquifer. However, because of the poor quality water, this represents a very hazardous source of replenishment. There is no evidence of deterioration in quality due to this source but the form of measurements carried out by the Commission are not sufficiently detailed to detect such changes.

An area of particular significance is that between Ironbark Creek (Portion 26, Parish of Scott) and the aquifer to the north and east. Here drilling on the Ironbark Line has shown poor quality water at depths from 40 feet. Changes in water level in bores in this line, especially B1, S2, suggest connection with the aquifer, so there is a definite possibility of contamination. This is part of the area in which geophysical resistivity measurements showed good quality water, so shallow near surface better quality water may offset the deeper poorer quality water. However, drilling did not detect any shallow water supply, either good or bad quality.



SALINE WATER INTRUSION:

The deterioration of water quality between occurrences of natural replenishment in the Giru area is an important factor and comes from two sources:

- (a) Sea water intrusion;
- (b) Saline water from older alluvials.

The threats are accentuated because of:

- (i) Very restricted localised aquifer which is heavily over exploited and whose sole replenishment is from runoff in the Haughton with little assistance from rainfall.
- (ii) Close proximity to coastal mud flats and areas of saline water even though the cultivated area is six miles from the sea.
- (iii) Base of the aquifer in the Haughton River around the Town of Giru and in the Anabranche section is below mean sea level for 18 miles upstream from its mouth, i. e. as far upstream as the present irrigation plants. This is upstream of the offtake of Ironbark Creek and of the Anabranche aquifer section. In February, 1967 users claimed that the aquifer was being pumped down to its base.
- (iv) Drilling of deep holes through the aquifer to bedrock without later proper sealing off has facilitated the intrusion of water.

The river is tidal as far as the railway bridge and salt water intrusion is felt at least two miles upstream of this. Analyses from Fordyce and Son's river pump (opposite Portion 17, Parish of Scott) show a conductivity range from 630 to 3500 micromhos/cm depending on the season.

As shown in Figures 6 to 18 and in the section on water quality, water from most of the investigation bores is highly saline and generally deteriorating in quality.

SAFE YIELD:

The ultimate objective of the investigation of any aquifer system is the determination of its safe yield. This is defined as "the amount of water which can be withdrawn from it annually without permanently depleting or damaging the aquifer". There are many factors which affect the results and the calculation is not as simple as it might first appear. For worthwhile results observations must be taken over a number of years and include the time of worst conditions.

The determination of the following properties of the aquifer is necessary to the calculation of the safe yield:

- (a) Properties obtained by observation include -
  - (i) extent, depth and thickness of the aquifer;

- (ii) seasonal variation in water level from the level when full to the lowest level on record;
  - (iii) variation in water quality in the aquifer and adjacent strata.
- (b) Properties obtained by calculation from properly conducted pump tests which are -
- (i) transmissibility of the aquifer (a measure of the flow of water through the aquifer);
  - (ii) storage coefficient (a coefficient indicative of the percentage of the aquifer occupied by water).

From the combination of information from the drilling programme and from landholders in respect of private bores, it is possible to obtain fairly accurate values for (a) (i), (ii) and (iii).

However, investigation drilling was concentrated on areas outside the aquifer and only two pump tests were carried out in the aquifer both of which were in the Anabbranch area. From this information and the data accumulated by the Commission on aquifer coefficients, it is estimated that 66 percent of the water stored in the aquifer can be extracted.

Table IV sets out the volume of water stored when the aquifer is full together with the volume available for use on the basis of the foregoing assumptions.

TABLE IV

Section	Surface Area (acs.)	Average Aquifer Thickness (feet)	Shape Factor	Specific Yield (%)	Volume of water stored (ac. ft.)	
					Maximum	Minimum
Haughton River	740	28	0.8	25	4,150	2,740
Anabbranch	1,365	28	0.8	20	6,110	4,040
Giru Delta	1,103	28	0.8	20	4,940	3,260
<b>TOTAL:</b>	<b>3,208</b>				<b>15,200</b>	<b>10,040</b>

The volumes set out in the above table are based on storage alone and do not account for any down river flow in the Haughton River Sands.

On the assumption that the Haughton River has one major fresh each year which is capable of replenishing the underground storage, it is reasonable to assume that the safe yield from the aquifer following full recharge is of the order of 10,000 acre feet.

DEFICIENCY IN SUPPLY FROM AQUIFER:

The area irrigated in the Giru area according to information from landholders is some 9,200 acres.

For information on actual use in the Burdekin Delta and in the Burdekin Irrigation Area for full irrigation the average annual irrigation application (in addition to rainfall) in the Giru area is estimated to be of the order of 30 inches. For an irrigated area of 9,200 acres this gives an average annual requirement for full irrigation of some 23,000 acre feet.

On this basis and assuming the irrigation use is spread uniformly throughout the year the supply available from the aquifer, provided the full storage can be utilised, would be sufficient to meet full requirements for some 160 days after it has been fully replenished, i. e. after the Haughton River flow has fallen below 30 to 40 cusecs.

As indicated under Haughton River Flows, stream flow records for 1952 to 1966 show that no flow periods of 160 or more days per year have occurred on eight occasions and varied from 168 to 345 days.

These can be subdivided into -

160 to 210 days	-	2 years
210 to 260 days	-	3 years
260 to 345 days	-	3 years

Figure 2 shows that rainfall in the Giru area between 1952 and 1966 have been substantially better than those which occurred between 1809 and 1952.

It can be expected therefore that the underground water supplies will be inadequate to meet full irrigation requirements in somewhat more than 50 percent of years.

EXTENT OF SHORTAGE OF SUPPLY:

The amount which available supplies fall short of full requirements will vary with periods of no flow in the Haughton River.

Supply required for an irrigated area of 9,200 acres and annual irrigation applications of 30 inches per acre for varying periods is approximately as follows:

50 days	-	3,200 acre feet
100 days	-	6,400 acre feet
150 days	-	9,600 acre feet

Thus if additional supply of 6,000 acre feet could be made available during periods of no river flow full irrigation requirements could be met in all but years such as 1957/58, 1961/62 and 1966/67.

An additional supply of some 10,000 acre feet would be necessary to meet full requirements in all years.

This additional supply would, however, only be effective if the aquifer can be fully drawn down without serious deterioration in water quality from salt water intrusion.

POSSIBLE METHODS OF IMPROVEMENT TO SUPPLY:

Provision of adequate good quality water for the existing area appears to require -

- (a) Prevention of salt water intrusion from the sea into the two main sections, the Haughton River alluvials and the Anabranh alluvials. This is to enable the full aquifer storage to be utilised with a minimum of deterioration in quality; and
- (b) Provision of additional supply.

Prevention of Sea Water Intrusion:

The aquifer in the Giru area is rather unique in that it is very limited in extent and from the information available the outlets or seaward extremities are limited in width and depth.

There are three of these, the Anabranh, Haughton River and Hodel sections.

Although no detailed investigations have been made it would appear practicable to construct an artificial barrier across these aquifers to serve the dual purposes of reducing salt water intrusion and leakage of fresh water from the aquifer.

If this is the case it would enable the aquifer to be fully drawn down with a lesser degree of deterioration in quality during periods of no flow in the river.

Some deterioration could still occur with water moving from the older Cainozoic alluvials into the aquifer but this movement must be slow due to the relatively low transmissibility of the older alluvials.

More detailed investigation of the practicability of these artificial barriers is considered desirable.

Provision of Additional Supply:

Additional supply during no flow periods of the Haughton River can only be provided by surface water storage. Such storage should be of sufficient capacity to give a yield of some 10,000 acre feet in 160 days following cease to flow in the Haughton River from which artificial replenishment of the aquifers could be provided as water levels are drawn down. Again no investigations have been made. The following alternatives are suggested for investigation:

- (a) Weirs on the Haughton River.

The following locations are proposed for investigation -

- (i) Weir in conjunction with artificial barrier to exclude sea water intrusion about  $1\frac{1}{2}$  miles downstream of the Railway Bridge between Portion 18V, Parish of Abbotsford and Portion 23V, Parish of Selkirk.
- (ii) A second weir in the vicinity of the Therbourne Bore Line about 1 mile above the Bruce Highway and as close as practicable to and downstream of the offtake of the Anabranh section of the aquifer from the Haughton River section.

Both of these structures would probably be required to be designed with collapsible crests such as fabridams to avoid aggravating floods.

- (iii) It is unlikely that weirs proposed in (i) and (ii) above would provide adequate additional supply and a third structure some distance further upstream would require investigation.

(b) Healey's Lagoon.

It would appear desirable to also investigate the possibility of increasing the storage of Healey's Lagoon by means of a weir structure with a collapsible crest between the old Townsville road and the Anabranh Bore Line together with levee banks on either side of the lagoon for some distance upstream.

This increased storage could at least provide additional supply for a number of pumping installations drawing water direct from the Lagoon.

It may also assist replenishment of underground supplies in the Anabranh section of the aquifer.

PROTECTION OF EXISTING SUPPLY:

Because of the limited supplies available from the aquifer in most years, the over development that has already occurred and the danger of increasing saline water intrusion by drilling beyond the base of the aquifer in the more recent alluvials into the older alluvials which contain much poorer quality water, it is considered desirable to establish control over any further drilling in the general Haughton River area.

This control can be established by declaration of the area as an "area of Sub-artesian Water Supplies" under the provisions of The Water Acts as has been the case with the Artesian Basin Area for over 40 years.

All new and existing bores must then be licensed and conditions imposed on the licenses to safeguard the existing supply as far as practicable, share it as equitably as practicable among users and avoid further over development.

It is considered that this control should be established even if works previously suggested for improvement to the supply are found practicable and implemented.

If established, it is envisaged that provisions of licenses would be directed ensuing that -

- (a) the area which landholders attempt to irrigate is not allowed to increase beyond the existing area unless assured supply is available for any such increase;
- (b) total annual use authorised for the whole area does not exceed  $2\frac{1}{2}$  acre feet per acre on 80 percent of the present gross assigned area able to obtain underground and surface supplies, or any increased area for which assured supplies can be provided;
- (c) annual quantities authorised to be used on individual holdings do not exceed  $2\frac{1}{2}$  acre feet per acre on 80 percent of existing gross assignments, or increased assignments for which assured supplies can be provided;
- (d) total authorised rates of withdrawals from existing or new bores on any individual holding will not exceed a rate which would allow irrigation of a maximum of 80 percent of the gross assigned area in a reasonable period such as pumping a quantity equivalent to 4 inches over the area in three weeks.

However, to ensure reasonably equitable sharing of supplies among the irrigators, once the river has ceased to flow, periods of pumping on individual holdings would require to be limited to ensure that overall rate of use for the area would not exceed a reasonable level such as 10,000 acre feet in five months;

- (e) to avoid aggravating the deterioration of quality of supplies by increasing movement from the poorer quality, supplies in the older alluvials be prohibited generally below the base of the more recent alluvials forming the aquifer.

If such drilling occurs such as in the Commission's investigation bores, steps be taken to adequately seal the holes below the level of the main aquifer.

To ensure that supplies available for natural replenishment of supplies in the Giru area are not further reduced, it is proposed that no further licenses for private diversion of surface water for irrigation be granted on the Haughton River catchment upstream of the general Giru area.

GEOLOGY AND GEOMORPHOLOGY

The principal units occurring in the area are shown in figure 1 (Scale 1" = 2 miles). The geology on this plan has been taken from the TOWNSVILLE and AYR Sheets, preliminary editions 1966 (Scale 1:250,000), from the most recent mapping by the Bureau of Mineral Resources, and the Queensland Geological Survey; by courtesy of the Director, Bureau of Mineral Resources, Geology and Geophysics.

By far the most dominant topographic features in the area are the sub-circular granite stocks of Mt. Elliot (4,000 ft.) and nearby Saddle Mountain (2,500 feet) which form a backdrop to the canelands at Giru. These have been highly resistant to erosion and consequently now rise abruptly from the coastal plain as high rugged ranges, deeply dissected in places, and mantled by dense scrub. These stocks are predominantly light coloured felspathic acidic granites. Apart from the Cainozoic sediments, these are the youngest rocks in the area, believed to be Permian to Mesozoic in age. Because of their dominant topographic position, these rocks would have been a generous source of material for the early Cainozoic and more recent alluvials.

The oldest rocks occurring in the area are Carboniferous to Permian in age, consisting of intermediate lavas and tuffs, with other minor acid volcanics. These rocks outcrop as low rounded foothills and seaward fringes to the more resistant Mt. Elliot granite beyond. It is possible that they might have some slight water potential, but they certainly do not represent a potential source for irrigation supplies. (These rocks represent, in part, an area which was previously identified by D.M. Traves in the 1950 mapping of the Townsville-Bowen Region as being Middle Devonian in age, equated to the Reid beds of limestones, tuffs and sandstones. With the revised mapping by the B.M.R. and Q.G.S., much of this Middle Devonian has been assigned a Carboniferous-Permian age).

The next oldest rock type occurring in the area is a granite of uncertain Carboniferous to Permian age. (Which was previously assigned by Traves as part of the Middle Devonian Reid Beds.) Topographically the outcrop is indistinguishable from and is a continuation of the same low foothills as the Carboniferous Volcanics and leads in a south easterly direction towards the Majors' Creek and Haughton River junction near the Cunningham Line. Granite such as this is not water bearing.

The strata occupying the greatest area extent on the map are the Cainozoic alluvials that occupy a flood plain which spreads from the foothills of Mt. Elliot, across the Haughton River, and the Barrattas to the Burdekin River including the Burdekin Delta. This plain is generally level with a slight slope towards the coast. Source material for these alluvials has been derived from the headwaters of the Haughton and Reid Rivers (Silurian to Devonian granodiorite, quartz sandstones, arkosic conglomerate), as well as from the local rock types previously described. These Cainozoic alluvials probably range in age from early Cainozoic (Pliocene) to Pleistocene, i.e. older than the sand and gravels in the present bed of the Haughton River.

The sequence is further described in the section on sub-surface geology and illustrated in the various sections (Fig. 6 - 18). In these sections the top of the older Cainozoic appears as a distinctive spotty red clay and probably represents oxidation of an older land surface. Where exposed at the surface, the principal rock type appears to be an arkosic conglomerate with very poor sorting, indication of deposition under torrential conditions. Pebbles and cobbles with quite random orientations are deposited

in rough layers separated by very clayey sands; the whole now much weathered and breaking down to clay. Exposures have been studied in a small creek on Portion 8, Parish of Scott, near the boundary with Parish of Abbottsford, in a small creek on the road crossing in Portion 7V, Parish of Scott, and in the Haughton River in the vicinity of the Cameron's Line, Poletti Line, Shirbourne Line and Old Road Line. The conglomerate is best exemplified at the Cameron's Line crossing, less so at the Poletti Line and even less so at the Shirbourne and Old Road Line Crossings. The rock type is not very robust, and under the influence of weathering it breaks down very easily. This is markedly shown in the rock bars which exist at the tram line crossing on the Old Road Line. Here, the rock underwater can be easily barred or picked out, and in places, breaks down to little more than a mud. The water potential of these Cainozoic sediments is not very great.

The Recent Cainozoic deposits consist of the Haughton River alluvials, the mud flats to the north which border Bowling Green Bay, and minor sand dunes. These alluvials are distributed in the present bed of the Haughton and in its former recent channels; the former Anabranche now marked by Healey's Lagoon and the minor delta in the vicinity of Giru township. On the ground and in aerial photographs, these former channels are marked by definite distinctive depressions, typical of these recent river deposits. The river alluvials contain the only worthwhile source for irrigation supplies in the area, and are extensively exploited as such by the cane farmers in the area. In depositing these alluvials, the Haughton has cut a path some 30 feet deep through the older Cainozoic reworking it and depositing it in its own bed. The light dirtier clay fraction, has in most cases, been taken further downstream and deposited in the mud flats that are building up round Bowling Green Bay. The irrigation potential of these aquifers is illustrated in the various sections (Figures 6 - 18).

A thin veneer of sandy deposits resulting from deposition from minor streams and possibly older beach deposits overlies portions of the older Cainozoic. Sometimes this contains fresh water but in other places the water is quite saline.

#### SUB-SURFACE GEOLOGY:

The record of the strata encountered in the Commission directed percussion drilling programme and of the strata in a number of private irrigation facilities and unsuccessful private test holes is shown on the sections figures 6 to 18. The drillers' descriptions have been retained and the sections present a factual record of the strata as encountered, but for simplicity many of the shorter intervals with minor differences in detailed description have been grouped under the one description.

The keys to the understanding of the sub-surface geology are:-

- (a) Recognition of the flood plain of older Cainozoic alluvials.
- (b) Recognition of these older alluvials in the bed of the Haughton River.
- (c) Recognition that the strata encountered in the bore holes must belong to these alluvials.
- (d) Recognition of the older weathering surface now marked by the formation of a spotty red clay varying from 12 - 20 feet beneath the present surface. Once recognised, this is seen to occupy a consistent stratigraphic position.



### A. 3.

- (e) Recognition of the channels which the Haughton River has recently cut through this older surface.
- (f) Recognition that these channels form one aquifer with similar aquifer characteristics and that in the Giru area this is the only worthwhile aquifer.
- (g) Recognition of the change in and increasing depth of strata, and the improvement in transmissibility, in water quality, in yield which takes place along the Townsville Road Line as one moves east from the Haughton River to the Barrattas Creeks.
- (h) Recognition of the Barrattas as marking the western limit of the influence from former channels of the Burdekin River. This is shown by the results above and results from The Dam Line B4 S7 and Cunningham Line B5 S7 and B1 S8; and is amply supported by regional geomorphology which suggests an older Burdekin River path breaking off above Claredale through Gladys Lagoon to the Barrattas.

Since they come from the same sources, there are many similarities in appearance and composition between the recent sands and gravels and the older alluvials. Thus some descriptions of sands and gravels in the older alluvials may not now be true sands and gravels but rather semi-consolidated to consolidated sediments, e. g. "clean coarse grained sand" or "dirty coarse grained sand and clay" (Townsville Road Line B3 S7, figure 13) and "brown sandy clay" or "claybound coarse grained sand and gravel" (Townsville Road Line B7, S6 Figure 13).

For simplicity however, the strata outside the known aquifer of the Haughton River, Anabranh and "Giru Delta" can be considered as consisting of clays, clayey sands and claybound gravels with very poor transmissibility, i. e. with very slow movement and poor yield of underground water. Along the Townsville Road from the Haughton River to Healey's Lagoon, the top 60' consists mainly of clay. In part this clay was present during deposition and in part it results from decomposition in situ, particularly noticeable in the breakdown of former pebbles to clay nodules.

APPENDIX B

WATER QUALITY

Analysis of water from Selected Facilities from Records of  
Bureau of Sugar Experimental Stations (Brandon) and Irrigation  
Commission.

Date	Conductivity mhos/cm.	Sodium Absorption Ratio	Equivalent NaCl from Cl. grains/gal.	ppm.
<u>McLennan &amp; Co., Portion 13V Parish of Selkirk</u>				
<u>4" Pump RM. 33</u>				
22.8.62	3970	8.5	109.1	1360
Feb, 1967	6350		162.0	1459
<u>6" Pump RM. 32</u>				
April, 1962	810	4.1	15.7	225
12.9.66	3100		87.5	1251
15.12.66	1760		43.6	623
23.2.67	975		20.0	286
<u>8" Old Pump RM. 34</u>				
April, 1962	6950	24.0	266.6	3812
Feb, 1967	6650		212.0	3032

## B. 2.

WATER QUALITY

Analysis of water from Selected Facilities from Records of  
Bureau of Sugar Experimental Stations (Brandon) and Irrigation  
Commission.



Date	Conductivity mhos/cm.	Sodium Absorption Ratio	Equivalent NaCl. from Cl. grains/gal.	ppm.
<u>A. Fordyce &amp; Son., Por. 17 Parish Scott.</u>				
<u>Pink Lily Pump RM52</u>				
March, 64	920		9.4	134
25.1.65	884	4.5	22.7	325
10.12.65	619	3.1	11.9	170
16.5.66	790		17.2	246
20.7.66	780		16.2	232
12.9.66	1780		53.8	769
15.12.66	2360		71.9	1028
21.2.67	760		14.0	200
<u>River Pump RM54</u>				
16.1.61			34.0	486
25.5.61			28.0	400
30.10.63	1990	7.5	60.4	864
25.1.65	627	2.9	11.4	163
23.11.65	3041	8.9	104.8	1499
10.12.65	1503	7.3	46.7	668
25.7.66	3578	10.0	121	1730
3.11.66	2738	8.8	89.0	1273
21.2.67	415		14.0	200
<u>Pierotti Brothers, Portion 12 Parish Scott</u>				
<u>Pump A - 5" Pump to 28 feet</u>				
2.3.65	5720	20.0	214	306
10.4.65	4654	11.3	176.9	2530
<u>Pump B - 6" Pump RM66</u>				
10.4.65	1337	5.9	25.1	359
<u>Pump D - 6" Pump</u>				
10.4.65	1192	4.2	31.8	455

WATER QUALITY

Analysis of water from Selected Facilities from Records of  
Bureau of Sugar Experimental Stations (Brandon).

Date	Conductivity mhos/cm.	Sodium Absorption Ratio	Equivalent NaCl. from Cl. grains/gal.	ppm.
<u>Donald Brothers, Portion 8V Parish Abbotsford.</u>				
<u>6" Pump JW42.</u>				
1.11.65	557	3.5	11.2	160
Feb, 67	910		18.0	257
<u>5" Pump JW43</u>				
29.11.65	444	2.0	6.8	97
Feb, 67	650		12.0	170
<u>4" Pump JW44</u>				
March, 64	660		8.8	126
21.10.65	350	2.3	5.1	73
21.12.65	470		9.2	133
16.5.66	1170		26.1	373
21.7.66	710		13.9	199
x 19.9.66	1484	3.8	25.0	358
+ 19.9.66	956	3.3	14.0	200
15.12.66	880		15.0	215
Feb, 67	1275		17.0	243
March, 67	760		16.0	229
x First sample at start of pumping				
+ Second sample after 16 hours pumping				
<u>Burry Brothers., Portion 11V Parish Abbotsford.</u>				
<u>Pump A RM62</u>				
10.7.61			39.9	371
29.11.63	1831	6.7	31.1	588
27.4.65	1963	6.4	56.8	812
<u>Pump B RM63</u>				
10.7.61			21.4	306
29.11.63	1331	6.0	29.0	415
27.4.64	1330	6.3	33.0	472
23.6.66	1696	5.6	41.2	589
<u>Pump C</u>				
10.7.61			50.2	718
Jan, 64	1720	8.4	42.2	603
20.7.66	2074	8.2	46.9	671
<u>Pump D, RM64</u>				

FIG. 1



**GEOLOGICAL LEGEND**

- |   |  |
|---|--|
| QUATERNARY                                | <span style="display:inline-block; width:15px; height:15px; background-color:orange; border:1px solid black;"></span> Qm Coastal mud flats                       |
|   | <span style="display:inline-block; width:15px; height:15px; background-color:lightorange; border:1px solid black;"></span> Qr Coastal sand dunes                 |
|   | <span style="display:inline-block; width:15px; height:15px; background-color:yellow; border:1px solid black;"></span> Qa Alluvials-aquifer                       |
| CAINOZOIC                                 | <span style="display:inline-block; width:15px; height:15px; background-color:lightyellow; border:1px solid black;"></span> Cza Alluvials & deltaic deposits      |
|   | <span style="display:inline-block; width:15px; height:15px; background-color:pink; border:1px solid black;"></span> P-Mg Epizonal adamellite & granite           |
| PERMIAN TO MESOZOIC                       | <span style="display:inline-block; width:15px; height:15px; background-color:lightpink; border:1px solid black;"></span> Pzug Granite, microgranite & adamellite |
|   | <span style="display:inline-block; width:15px; height:15px; background-color:lightblue; border:1px solid black;"></span> C-Pv Intermediate lavas & pyroclastics  |
| - - - - - Geological Boundary Approximate |  |







NOTE:- Geology adapted from Townsville and Ayr sheets - preliminary editions 1966 (scale - 1:250,000) - mapping by Bureau of Mineral Resources & Qld. Geological Survey

**CONTOUR LEGEND**


Level of base of cainozoic sediments 40 feet below State Datum shown thus  $-40'$   
(Equivalent to top of permo-carboniferous weathered granite and volcanics.)

Scale of Miles

QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
**HAUGHTON RIVER**  
GROUNDWATER INVESTIGATION  
GENERAL PLAN SHOWING  
GEOLOGY AND BEDROCK CONTOURS



QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
HAUGHTON RIVER  
GROUNDWATER INVESTIGATIONS  
**AYR AND GIRU  
RAINFALL**



**GEOLOGICAL LEGEND**


- QUATERNARY
  - Qm Coastal mud flats
  - Qa Alluvials - Aquifer
  - Cza Alluvials & deltaic deposits
- CAINOZOIC
- PERMIAN TO MESOZOIC
  - P-Mg Epizonal adamellite & granite
- CARBONIFEROUS TO PERMIAN
  - C-Pv Intermediate lavas & pyroclastics
- Geological Boundary Approximate

NOTE:- Geology adapted from Townsville and Ayr sheets - preliminary editions 1966 (scale - 1:250,000) - mapping by Bureau of Mineral Resources & Qld. Geological Survey

**WATER QUALITY LEGEND**

0 - 200	micromhos/cm.	●
200 - 500	" "	●
500 - 1000	" "	●
1000 - 2000	" "	●
2000 - 5000	" "	●
5000 - 40000	" "	●
Depth of sample in Feet		SI

Conductivity at 25°C. in micromhos/cm. - 1967



QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
HAUGHTON RIVER  
GROUNDWATER INVESTIGATION  
**DEVELOPED AREA SHOWING  
GEOLOGY AND WATER QUALITY**



**LEGEND**

Areas Irrigated 1965-1966 . . . . .

Irrigation pump from Surface Water . . . . .



Irrigation pump from spears in Haughton River . . . . .

Irrigation pump from shallow bore . . . . .

Scale of Chains  
40 20 0 40 80 120

QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
HAUGHTON RIVER  
GROUNDWATER INVESTIGATION  
DEVELOPED AREA SHOWING  
IRRIGATED AREAS





**LEGEND**

- Alluvials - Aquifer
- Investigation Bore with Pilot Pipe inserted
- Investigation Bore without Pilot Pipe - Dry
- Investigation Production Bore (Storage Coefficient Determined)
- Commission Gauge Board
- Investigation Bore Line

Scale of Miles



2 1 0 2 4 6

QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
HAUGHTON RIVER  
GROUNDWATER INVESTIGATION  
**INVESTIGATION BORES & BORE LINES**


BORE No. / SITE No.	Commenced / Completed	B6 S1 / July 1964	B2 S2 / June 1964	B3 S3 / June 1964	B4 S4 / July 1964	B7 S5 / August 1964
Drilling Time	hrs.					
Other Productive Time	hrs.					
SCREEN SETTINGS		Bore not Screened	Bore not Screened	Bore not Screened	Bore not Screened	Bore not Screened
PUMP TEST No.		No Test	No Test	No Test	No Test	No Test
PUMP TYPE						
SUCTION AT						
DATE		15-7-64	8-6-64	10-6-64	15-7-64	18-8-64
S.W.L. (below N.S.)		24'-0"	Dry	24'-0"	25'-0"	Dry
AVAILABLE D.D.						
DURATION						
FINAL PUMP RATE G.P.H.						
FINAL D.D.						
RECOVERY TIME						
RESIDUAL D.D.						
WATER QUALITY	Location	No Sample	No Sample	No Sample	No Sample	No Sample
	Conductivity at 25°C					
	Total Solids					
	Chlorides as Cl <sup>-</sup>					
	Alkalinity					
	Hardness					
	pH					
REMARKS		Casing removed. No pilot pipe inserted.	Casing removed. No pilot pipe inserted. N.S.R.L. 79-01	Casing removed. No pilot pipe inserted. N.S.R.L. 70-68	Casing removed and pilot pipe inserted. Ref. pt. is top of 2" G.I. pipe with cap removed.	Casing removed. No pilot pipe inserted.

All bores drilled 8" dia. for full depth by contract diller.

BORE No. / SITE No.	Commenced / Completed	B5 S7 / 21-10-65 / 5-11-65	B1 S8 / 30-9-65 / 20-10-65
Drilling Time	hrs.	13 1/4	22 1/2
Other Productive Time	hrs.	68	50 1/4
SCREEN SETTINGS		59'-9" Top Packer 60'-3" Bot. Casing 1 x 0-036 1 x 0-050 66'-5" Bot Cap. 6" Willscreens.	74'-0" Top Packer 75'-6" Bot. Casing 3 x 0-098" 83'-6" Bot Cap. 6" Willscreens.
PUMP TEST No.		2	1, 2
PUMP TYPE		Pomona	Pomona, Pomona
SUCTION AT		59'-0"	72'-6", 72'-6"
DATE		3-11-65	14-10-65, 19-10-65
S.W.L. (below N.S.)		34'-9"	29'-2", 29'-2"
AVAILABLE D.D.		24'-3"	43'-4", 43'-4"
DURATION		360 mins.	360 mins., 360 mins.
FINAL PUMP RATE G.P.H.		27,300	31,500, 31,800
FINAL D.D.		22'-3"	19'-4 1/2", 19'-5 1/2"
RECOVERY TIME		60 mins.	60 mins., 60 mins.
RESIDUAL D.D.		2 1/4"	4", 3 1/2"
WATER QUALITY	Location	42'-6"	70 ft. to 84 ft.
	Conductivity at 25°C	4.25	5.35
	Total Solids		320
	Chlorides as Cl <sup>-</sup>		65
	Alkalinity		2.50
	Hardness		80
	pH		8.3
	Date	15-12-66	6-10-65
REMARKS		5 1/2 galls. of sand removed in 2 1/2 hours by bailing, shock and solid surging in screens. Casing & screens removed. Pilot pipe inserted. Ref. pt. is top of 6" guard with lid removed.	22 1/4 galls. of sand removed in 6 hours by bailing, shock and solid surging in screens. Casing & screens removed. Pilot pipe inserted. Ref. pt. is top of 6" guard with lid removed.



**LEGEND**  
 [Symbol] Aquifer  
 c.g. Coarse grained  
 & With  
 LEVEL BOOKS: 14297, 14298, 14299, 14300, 14301, 14302, 14303, 14312



QUEENSLAND  
 IRRIGATION AND WATER SUPPLY COMMISSION  
**HAUGHTON RIVER**  
 GROUND WATER INVESTIGATION  
**CUNNINGHAM LINE**

BORE No. / SITE No.	Commenced / Completed	B1	B6	B2	B5	B7	B3	B8	B9
		20-8-64 / 31-8-64	9-2-65 and 23-3-65 / 26-2-65 and 1-4-65	1-9-64 / 14-9-64	20-1-65 / 9-2-65	26-2-65 / 9-3-65	16-9-64 / 21-9-64	1-4-65 / 14-4-65	13-5-65 / 2-6-65
Drilling Time hrs.			32 / 74 1/4		32 1/2 / 22 1/2	34 1/2 / 15		21 1/2 / 16 1/2	33 1/2 / 50 3/4
Other Productive Time hrs.									
SCREEN SETTINGS		Bore not screened	56'-6" Top of Packen. 59'-2" Bottom of Casing. 2 x 0-050" x 6" Willscreens. 63'-0" Bottom of Cap.	Bore not screened	Bore not screened	Bore not screened	Bore not screened	Bore not screened	111'-7" Top Packen. 113'-10" Bot. Casing. 1 x 0-050" x 6" Willscreens. 123'-5" Bot. Cap. 6" Willscreens.
PUMP TEST No.		No Test	1	No Test	No Test	No Test	No Test	No Test	1
SUCTION AT			1						1
DATE		31-8-64 / 15-12-66	31-3-65 / 15-12-66	23-11-64 / 14-9-66	16-3-65 / 15-12-66	16-3-65 / 15-12-66	17-9-64 / 15-12-66	3-11-65 / 15-12-66	31-5-65
S.W.L. (below N.S.)		4'-8" / 8'-11"	3'-1"	4'-11" / 5'-6"	5'-6" / 8'-11"	11'-4" / 16'-8"	12'-4" / 9'-8"	15'-0" / 17'-5"	3'-1"
AVAILABLE DD			53'-5"	60 mins.					93'-10"
DURATION			60 mins.						60 mins.
FINAL PUMP RATE G.P.H.			1,200						2,200
FINAL DD			45'-4"						48'-0"
RECOVERY TIME			30 mins.						12 mins.
RESIDUAL DD			0'-5 1/2"						3'-7"
Location		21'-8" / 21'-8"	8'-0" / 23'-0"	54 to 62 ft. / 68 to 71 ft. / 77 to 82 ft.	136'-6" / 91'-0"	25'-0" / 84 to 96 ft.	66'-8" / 21'-0" / 82'-10"	39 to 41 ft. / 113 to 123 ft.	
WATER QUALITY		11,500 / 4,000	21,000 / 17,000	6,180 / 7,300	12,450 / 33,000	21,000 / 5,920	9,700 / 9,700 / 9,500	860 / 436	
Total Solids		2,649 / 2,420	15,520 / 11,200	2,850 / 4,450	7,500 / 20,000	5,000 / 3,400	6,380 / 5,700	51 / 246	
Chlorides as Cl <sup>-</sup>		1,030 / 1,030	8,000 / 5,800	1,600 / 2,200	17,400 / 3,800	4,720 / 3,800	3,500 / 3,540	182 / 64	
Alkalinity		25 / 25	0 / 0	120 / 256	150 / 256	315 / 315	260 / 310	176 / 128	
Hardness		900 / 300	3,200 / 0	400 / 750	1,310 / 11,360	1,896 / 530	880 / 880	60 / 68	
pH		6-5 / 6-5	5-1 / 6-1	7-9 / 7-1	7-0 / 7-0	7-2 / 7-0	7-7 / 8-0	8-1 / 7-5	
Date		14-9-66 / 18-4-67	10-2-65 / 10-2-65	11-2-65 / 11-2-65	4-10-66	4-10-66	1-3-65 / 4-3-65	18-5-65 / 31-5-65	

BORE No. / SITE No.	Commenced / Completed	B10A	B10	B11	B12	B12A	
		28-6-65 / 14-7-65	2-6-65 / 25-6-65	5-11-64 / 23-11-64	5-8-65 / 20-8-65	2-0-65 / 21-11-65	
Drilling Time hrs.		12	26	47	32 1/2	34 1/2	
Other Productive Time hrs.		35 3/4	66	44 1/4	27 1/4	314	
SCREEN SETTINGS		76'-11" Top Packen. 78'-3" Bot. Casing. 2 x 0-073" 86'-0" Bot. Cap. 6" Willscreens.	81'-2" Top of Packen. 83'-0" Bottom of Casing. 2 x 0-073" 1 x 0-060" 1 x 0-050" 93'-0" Bottom of Cap.	Bore not screened	Bore not screened	51'-2" Top Packen. 52'-2" Bot. Casing. 1 x 0-073" 3 x 0-098" 63'-0" Bot. Cap. 6" Willscreens.	81'-6" Top Packen. 82'-9" Bot. Casing. 1 x 0-073" 3 x 0-098" 93'-4" Bot. Cap. 6" Willscreens.
PUMP TEST No.		2	2	No Test	No Test	2	
SUCTION AT		Pomona	Pomona			Pomona	
DATE		9-7-65 / 9-7-65	23-6-65	11-8-65		28-10-65 / 12-11-65	
S.W.L. (below N.S.)		25'-9" / 25'-10"	25'-0"	23'-10"		12'-11-65 / 12-11-65	
AVAILABLE DD		47'-11"	51'-0"			19'-7" / 19'-11"	
DURATION		360 mins.	390 mins.			360 mins. / 360 mins.	
FINAL PUMP RATE G.P.H.		15,600	18,100			120 mins. / 120 mins.	
FINAL DD		44'-0 1/2"	44'-9"			84'-4 1/2" / 1'-6 3/4"	
RECOVERY TIME		30 mins.	30 mins.			60 mins. / 60 mins.	
RESIDUAL DD		0'-1 1/4"	0'-2 1/2"			60 mins. / 60 mins.	
Location		No Sample	29'-0" / 103 to 107 ft. / 149'-0"	89'-2"	41'-0" / 80 to 86 ft. / 112'-0"	End of test 2	
WATER QUALITY			540 / 378 / 428 / 665	436 / 310 / 400 / 338	208 / 136 / 138	610 / 366 / 125	
Total Solids			323 / 220 / 240 / 384	260 / 171 / 230 / 203	24 / 22 / 22	88 / 98 / 115	
Chlorides as Cl <sup>-</sup>			68 / 32 / 48 / 52	80 / 38 / 38 / 32	56 / 106 / 24	52 / 52	
Alkalinity			196 / 160 / 144 / 260	124 / 108 / 146 / 132	88 / 98 / 115	80	
Hardness			120 / 100 / 92 / 80	120 / 86 / 106 / 24	52 / 52	80	
pH			8-0 / 8-2 / 8-1 / 8-1	7-5 / 7-6 / 8-1 / 8-0	7-8 / 8-4	8-5	
Date			3-6-65 / 23-6-65 / 7-6-65 / 8-6-65	4-10-66	6-8-65 / 9-8-65 / 10-8-65	12-11-65	

REMARKS

All bores drilled 8" dia. For full depth.

Casing removed and pilot pipe inserted.

Ref. pt. is top of 2" G.I. pipe with cap removed.

Contract drilled.

Ref. pt. is top of G" guard with lid removed.

27 1/2 gallons of sand removed in 23 1/2 hours by bailing, shock and valve surging in screens and casing.

Casing and screens removed and pilot pipe inserted.

Ref. pt. is top of G" guard with lid removed.

Casing removed and pilot pipe inserted.

Ref. pt. is top of 2" G.I. pipe with cap removed.

Contract drilled.

Cement-bentonite seal placed 77 to 87 ft. and 91 to 101 ft.

Casing removed and pilot pipe inserted.

Ref. pt. is top of G" guard with lid removed.

Ref. pt. is top of G" guard with lid removed.



Contract Drilled.

49 3/4 gallons of sand removed in 12 hours by bailing, shock and valve surging.

Casing removed.

Pilot pipe inserted.

Ref. pt. is top of G" guard with lid removed.



LEGEND

- Aquifer
- Gp Gravel
- cg Coarse Grained
- fg Fine Grained
- W With
- Natural Surface Levels taken from Main Roads Survey

QUEENSLAND IRRIGATION AND WATER SUPPLY COMMISSION



**HAUGHTON RIVER**  
GROUND WATER INVESTIGATION

**TOWNSVILLE ROAD LINE**


BORE No.	Commenced	B2	B3	B4	B5
SITE No.	Completed	S2	S3	S4	S5
Drilling Time	hrs.	June 1964	June 1964	June 1964	June 1964
Other Productive Time	hrs.				
SCREEN SETTINGS		Bore not screened	Bore not screened	Bore not screened	Bore not screened
PUMP TEST No.		No Test	No Test	No Test	No Test
PUMP TYPE					
SUCTION AT					
DATE		17-6-64	24-6-64	25-6-64	7-6-64
S.W.L. (Below N.S.)		Dry	Dry	Dry	Dry
AVAILABLE D.D.					
DURATION					
FINAL PUMP RATE G.P.H.					
FINAL D.D.					
RECOVERY TIME					
RESIDUAL D.D.					
WATER QUALITY	Location				
in	Conductivity at 25°C				
Micromhos per cm & ppm.	Total Solids				
	Chlorides as Cl <sup>-</sup>				
	Alkalinity				
	Hardness				
	pH				
REMARKS					
		All bores drilled 8" dia for full depth. All bores contract drilled.	Casing removed. No pilot pipe inserted.	Casing removed. No pilot pipe inserted.	Casing removed. No pilot pipe inserted.

BORE No.	Commenced	Completed
Drilling Time	hrs.	
Other Productive Time	hrs.	
SCREEN SETTINGS		
PUMP TEST No.		
PUMP TYPE		
SUCTION AT		
DATE		
S.W.L.		
AVAILABLE D.D.		
DURATION		
FINAL PUMP RATE G.P.H.		
FINAL D.D.		
RECOVERY TIME		
RESIDUAL D.D.		
WATER QUALITY	Location	
in	Conductivity at 25°C	
Micromhos per cm & ppm.	Total Solids	
	Chlorides as Cl <sup>-</sup>	
	Alkalinity	
	Hardness	
	pH	
REMARKS		





**LEGEND**  
 Aquifer  
 With  
 LEVEL BOOK : 14303



QUEENSLAND  
 IRRIGATION AND WATER SUPPLY COMMISSION  
 HAUGHTON RIVER  
 GROUND WATER INVESTIGATION  
**CAMERONS LINE**

BORE No. SITE No.	Commenced Completed	B6 S1	B2 S2	B3 S3	B4 S4
		July 1964	June 1964	June 1964	July 1964
Drilling Time	hrs.				
Other Productive Time	hrs.				
SCREEN SETTINGS		Bore not screened.	Bore not screened.	Bore not screened.	Bore not screened.
PUMP TEST No.		No Test	No Test	No Test	No Test
PUMP TYPE					
SUCTION AT					
DATE		15-7-64	8-6-64	10-6-64	15-7-64
S.W.L. (Below N.S.)		24'-0"	Dry	24'-0"	25'-0"
AVAILABLE D.D.					
DURATION					
FINAL PUMP RATE G.P.H.					
FINAL D.D.					
RECOVERY TIME					
RESIDUAL D.D.					
WATER QUALITY	Location	No Sample		No Sample	No Sample
	Conductivity at 25°C				
	Total Solids				
	Chlorides as Cl <sup>-</sup>				
	Alkalinity				
	Hardness				
	pH				
REMARKS		All bores drilled 8" dia. for full depth by contract driller.	Casing removed. No pilot pipe inserted.	Casing removed. No pilot pipe inserted.	Casing removed. No pilot pipe inserted. Ref. pt. is top of 2" G.I. pipe with cap removed.


BORE No. SITE No.	Commenced Completed
Drilling Time	hrs.
Other Productive Time	hrs.
SCREEN SETTINGS	
PUMP TEST No.	
PUMP TYPE	
SUCTION AT	
DATE	
S.W.L.	
AVAILABLE D.D.	
DURATION	
FINAL PUMP RATE G.P.H.	
FINAL D.D.	
RECOVERY TIME	
RESIDUAL D.D.	
WATER QUALITY	Location
	Conductivity at 25°C
	Total Solids
	Chlorides as Cl <sup>-</sup>
	Alkalinity
	Hardness
	pH
REMARKS	



LEGEND



Aquifer  
c.g. Coarse grained  
c. With

LEVEL BOOKS : 14297  
14298  
14299  
14300  
14301  
14302  
14312



QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
HAUGHTON RIVER  
GROUND WATER INVESTIGATION  
CUNNINGHAM LINE  
(HAUGHTON RIVER SECTION)



BORE No.	Commenced	LM37	B2	B4	8-11-65
SITE No.	Completed	May 1966	S2	S7	26-11-65
Drilling Time	hrs.				23
Other Productive Time	hrs.				79 1/4
SCREEN SETTINGS		0' N.S. 2x5" spears. 13' Gauge. 16'	Bore not screened.	81'-0" Top Packer. 83'-1" Bot. Casing. 1x0.060" 2x0.050" 1x0.036" 95'-0" Bot. Cap. 6" Willscreens.	53'-0" Top of Packer. 54'-7" Bot. of Casing. 1x0.050" 1x0.036" 61'-5" Bot. of Cap. 6" Willscreens.
PUMP TEST No.		No Test	No Test	1	2
PUMP TYPE				Bailer test.	Pomona. Bailer Test.
SUCTION AT				48'-8"	
DATE		1-2-67	22-7-64	16-11-65	23-11-65
S.W.L. (below N.S.)		8'-0"	40'-0"	29'-5"	30'-8"
AVAILABLE D.D.				51'-7"	18'-0"
DURATION				20 mins.	360 mins.
FINAL PUMP RATE G.P.H.				400	4,800
FINAL D.D.				51'-7"	15'-1 1/2"
RECOVERY TIME				30 mins.	20 mins.
RESIDUAL D.D.				3'-3"	0'-1 1/2"
WATER QUALITY	Location	No sample	No sample	Bailer Test 1	No sample
	Conductivity at 25°C			240	
	Total Solids			145	
	Chlorides as Cl <sup>-</sup>			25	
	Alkalinity			75	
	Hardness			25	
	pH			8.5	
	Date			16-11-65	
REMARKS		Private Water Facility. Normal pump rate 45,000 g.p.h. Seasonal variation N.S. to 8 ft.	Casing removed. No pilot pipe inserted. Contract drilled.	79 galls. of sand removed in 13 hours by bailing, shock and solid surging in screens.	94 1/2 galls. of sand removed in 11 hours by bailing, shock, solid and valve surging.
				12 1/2 galls. of sand removed in 15 hours by bailing, shock, solid and valve surging. Casing and screens removed. Pilot pipe instd.	
				Ref. pt. is top of 6" guard with cap removed.	



**LEGEND**  
 Aquifer  
 c.g. Coarse Grained  
 LEVEL BOOK : 14304

QUEENSLAND  
 IRRIGATION AND WATER SUPPLY COMMISSION  
**HAUGHTON RIVER**  
 GROUND WATER INVESTIGATION  
**THE DAM LINE**

BORE No.	Commenced	B2	25-11-64	LM29	1965	B1	12-11-64
SITE No.	Completed	S1	3-12-64			S3	16-11-64
Drilling Time	hrs.						
Other Productive Time	hrs.						
SCREEN SETTINGS	Bore not Screened	0'-N.S. 12' Conc. Well. 3x5" spears. 33' Gauze. 36'		Bore not Screened			
PUMP TEST No.	No Test	No Test	No Test	No Test		No Test	
PUMP TYPE							
SUCTION AT							
DATE	2-12-64	15-12-66	1-2-67	14-11-64	15-12-66		
S.W.L. (below N.S.)	21'-0"	23'-7"	Est. 33'-0"	21'-0"	21'-7"		
AVAILABLE D.D.							
DURATION							
FINAL PUMP RATE G.P.H.							
FINAL D.D.							
RECOVERY TIME							
RESIDUAL D.D.							
WATER QUALITY	Location	71'-0"	No Sample	56'-5"			
	Conductivity at 25°C	1060		2225			
	Total Solids	638		1365			
	Chlorides as Cl <sup>-</sup>	88		420			
	Alkalinity	488		620			
	Hardness	196		140			
	pH	7.3		8.2			
	Date	4-10-66		4-10-66			
REMARKS	Casing removed & pilot pipe inserted. Ref. pt. is top of 6" guard.- Lid removed. Contract Drilled.	Private Water Facility Normal pump rate 30,000 g.p.h. Seasonal variation N.S. to 33 ft.		Casing removed & pilot pipe inserted. Ref. pt. is top of 6" guard.- Lid removed. Contract Drilled.			
BORE No.	Commenced						
SITE No.	Completed						
Drilling Time	hrs.						
Other Productive Time	hrs.						
SCREEN SETTINGS							
PUMP TEST No.							
PUMP TYPE							
SUCTION AT							
DATE							
S.W.L.							
AVAILABLE D.D.							
DURATION							
FINAL PUMP RATE G.P.H.							
FINAL D.D.							
RECOVERY TIME							
RESIDUAL D.D.							
WATER QUALITY	Location						
	Conductivity at 25°C						
	Total Solids						
	Chlorides as Cl <sup>-</sup>						
	Alkalinity						
	Hardness						
	pH						
REMARKS							




LEGEND

Aquifer  
c.g. Coarse grained  
f. With



LEVEL BOOK: 14294  
14308

SCALE




QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
HAUGHTON RIVER  
GROUND WATER INVESTIGATION  
POLETTI LINE

BORE No.	Commenced	B1	LM5	B3	B2
SITE No.	Completed	S2	1952	S4	SG
Drilling Time	hrs.				
Other Productive Time	hrs.				
SCREEN SETTINGS		Bore not screened	3 x 6" spears 18' Gauze. 21'	Bore not screened	Bore not screened
PUMP TEST No.		No Test	No Test	No Test	No Test
PUMP TYPE					
SUCTION AT					
DATE		21-10-64	15-12-66	2-2-67	14-12-64
S.W.L. (below N.S.)		18'-6"	19'-6"	Est. 17 ft.	28'-0"
AVAILABLE D.D.					Blocked.
DURATION					
FINAL PUMP RATE G.P.H.					
FINAL D.D.					
RECOVERY TIME					
RESIDUAL D.D.					
WATER QUALITY		Location	126'-8"	18 ft. to 21 ft.	64'-2"
		Conductivity at 25°C	6,300	615	3,100
		Total Solids	395		1,820
		Chlorides as Cl <sup>-</sup>	2,120		1,059
		Alkalinity	480		440
		Hardness	600		430
		pH	7.7		400
		Date	4-10-66	17-2-67	7.5
					7.3
REMARKS		Casing removed and pilot pipe inserted.	Private Water Facility Normal pump rate 45,000 g.p.h. Seasonal variation N.S. to 19 ft.	Casing removed and pilot pipe inserted.	Casing removed and pilot pipe inserted.
				Ref. pt. is top of 2" G.I. pipe with cap removed.	Ref. pt. is top of 2" G.I. pipe with cap removed.
BORE No.	Commenced				
SITE No.	Completed				
Drilling Time	hrs.				
Other Productive Time	hrs.				
SCREEN SETTINGS					
PUMP TEST No.					
PUMP TYPE					
SUCTION AT					
DATE					
S.W.L.					
AVAILABLE D.D.					
DURATION					
FINAL PUMP RATE G.P.H.					
FINAL D.D.					
RECOVERY TIME					
RESIDUAL D.D.					
WATER QUALITY					
REMARKS					



**LEGEND**  
 Aquifer



Fig. Fine Grained  
 & With  
 LEVEL BOOK: 14307  
 14294



QUEENSLAND  
 IRRIGATION AND WATER SUPPLY COMMISSION  
**HAUGHTON RIVER  
 GROUND WATER INVESTIGATION  
 SHIRBOURNE LINE**



BORE No.	Commenced	B7	26-2-65	B3	16-9-64	B8	1-4-65
SITE No.	Completed	S6	9-3-65	S7	21-9-64	S10	14-4-65
Drilling Time	hrs.	34 1/2				21 1/2	
Other Productive Time	hrs.	15				16 1/2	
SCREEN SETTINGS		Bore not Screened		Bore not Screened		Bore not Screened	
PUMP TEST No.		No Test		No Test		No Test	
PUMP TYPE							
SUCTION AT							
DATE		16-3-65	15-12-66	17-9-64	15-12-66	3-11-65	15-12-66
S.W.L. (below N.S.)		11'-4"	16'-8"	12'-4"	9'-8"	15'-0"	17'-5"
AVAILABLE D.D.							
DURATION							
FINAL PUMP RATE G.P.H.							
FINAL D.D.							
RECOVERY TIME							
RESIDUAL D.D.							
WATER QUALITY	Location	25 ft.	84 ft.-96 ft.	66'-8"	21'-0"	82'-10"	
	Conductivity at 25°C	21,000	5,920	9,700	9,700	9,500	
	Total Solids	15,100	3,400	5,900	6,380	5,700	
	Chlorides as Cl <sup>-</sup>	8,900	1,600	4,000	3,500	3,540	
	Alkalinity	116	336	76	260	310	
	Hardness	3,660	530	1,896	940	880	
	pH	7.2	7.0	7.5	7.7	8.0	
	Date	1-3-65	4-3-65	4-10-66	9-4-65	4-10-66	
REMARKS		All bores drilled 8" dia. for full depth.	Casing removed and pilot pipe inserted. Ref. pt. is top of 6" guard with lid removed.	Casing removed and pilot pipe inserted. Ref. pt. is top of 2" G.I. pipe with cap removed. Contract Drilled	Casing removed and pilot pipe inserted. Ref. pt. is top of 6" guard with lid removed.		
BORE No.	Commenced	AB37	14-10-66	RM96	1964	RM82	RM26
SITE No.	Completed						
Drilling Time	hrs.						
Other Productive Time	hrs.						
SCREEN SETTINGS				0' N.S. Earth Well. 9' 2x 4" spears. 28' Gauze. 32'	0' N.S. 6 x 3" spears. 18' 20" Gauze.		
PUMP TEST No.		No Test		No Test		No Test	
PUMP TYPE							
SUCTION AT							
DATE				1-2-67		27-1-67	
S.W.L. (below N.S.)				26'-0"		17'-0"	
AVAILABLE D.D.							
DURATION							
FINAL PUMP RATE G.P.H.							
FINAL D.D.							
RECOVERY TIME							
RESIDUAL D.D.							
WATER QUALITY	Location	No sample		No sample		28 ft. to 32 ft.	
	Conductivity at 25°C					370	
	Total Solids						
	Chlorides as Cl <sup>-</sup>						
	Alkalinity						
	Hardness						
	pH						
	Date					21-2-67	
REMARKS		Unsuccessful private 3" test bore. Struck soak at 18 ft. Struck saline water at 23 ft.	Unsuccessful private 3" test bore. Struck soak at 30 ft.	Private Water Facility. Normal pump rate 20,000 g.p.h. Seasonal variation 14 ft. to 26 ft.	Private Water Facility. Normal pump rate 40,000 g.p.h. Seasonal variation N.S. to 17 ft.		




**LEGEND**

Aquifer

c.g. Coarse grained  
f.g. Fine grained  
W. With



LEVEL BOOK : 14309




QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION

**HAUGHTON RIVER**  
**GROUND WATER INVESTIGATION**  
**TOWNSVILLE ROAD LINE**  
**(HAUGHTON RIVER SECTION)**

BORE No. SITE No.	Commenced Completed	RM52. After 1960	RM53 1965	B4 S8	2-10-64 13-10-64
Drilling Time	hrs.				
Other Productive Time	hrs.				
SCREEN SETTINGS		0' N.S. 16 x 2" Spears. 2 x 3" Spears. 20' Gauze 23' Gauze	0' N.S. G.I. Well. 7 x 3" Spears. 37' Gauze 40' Gauze	Bore not screened.	
PUMP TEST No.		No Test	No Test	No Test	
PUMP TYPE					
SUCTION AT					
DATE		1-2-67	1-2-67	23-11-64	15-12-66
S.W.L. (below N.S.)		Est. 19 ft.	Est. 26 ft.	13'-5"	14'-2"
AVAILABLE D.D.					
DURATION					
FINAL PUMP RATE G.P.H.					
FINAL D.D.					
RECOVERY TIME					
RESIDUAL D.D.					
WATER QUALITY in Micromhos per cm & ppm.	Location	20 to 23 ft.	No sample.	158'-3"	
	Conductivity at 25°C	760		2,360	
	Total Solids			1,380	
	Chlorides as Cl <sup>-</sup>			692	
	Alkalinity			112	
	Hardness			224	
REMARKS	Date	21-2-67		4-10-66	
	Private Water Facility. Normal pump rate 60,000 g.p.h. Seasonal variation 8 to 19 ft. Ref. pt. is top of open 2" test spear.		Private Water Facility. Normal pump rate 60,000 g.p.h. Seasonal variation 14 to 26 ft.		Drilled 8" dia. for full depth by Contractor. Casing removed and pilot pipe inserted. Ref. pt. is top of 2" G.I. pipe with cap removed. Previously recorded as B4S8 - Townsville Road Line.





**LEGEND**  
 Aquifer  
 LEVEL BOOK: 14308  
 14312




QUEENSLAND IRRIGATION AND WATER SUPPLY COMMISSION  
**HAUGHTON RIVER**  
 GROUND WATER INVESTIGATION  
**OLD ROAD LINE**

BORE No. SITE No.	Commenced Completed	B3 15-4-65 S5 22-4-65	4-5-65	B4 5-5-65 S6 12-5-65	B2 17-11-64 S1 19-11-64	B1 28-10-64 S2 4-11-64	LM8 22-8-60
Drilling Time hrs.		16 1/2		22 1/2			
Other Productive Time hrs.		6 3/4		6 1/2			
SCREEN SETTINGS		Bore not screened.		Bore not screened.		Bore not screened.	Bore not screened.
PUMP TEST No.		No Test.		No Test.		No Test.	No Test.
PUMP TYPE							
SUCTION AT							
DATE		11-5-65	15-12-66	11-5-65	13-9-66	19-11-64	15-12-66
S.W.L. (below N.S.)		10'-1"	11'-3"	11'-0"	12'-8"	17'-3"	14'-0"
AVAILABLE D.D.						23'-6"	27'-7"
DURATION							
FINAL PUMP RATE G.P.H.							
FINAL D.D.							
RECOVERY TIME							
RESIDUAL D.D.							
WATER QUALITY	Location	40'-0"		52'-7"		50'-11"	
	Conductivity at 25°C	3,500		4,850		6,250	
	Total Solids	2,328		2,890		4,017	
	Chlorides as Cl <sup>-</sup>	1,140		1,120		1,970	
	Alkalinity	440		880		520	
	Hardness	220		252		1,130	
	pH	8.2		8.4		7.1	
	Date	21-4-65		7-5-65		4-10-66	
REMARKS		Casing removed and pilot pipe inserted. Ref. pt. is top of G <sup>2</sup> guard with lid removed.		Casing removed and pilot pipe inserted. Ref. pt. is top of G <sup>2</sup> guard with lid removed.		Casing removed and pilot pipe inserted. Ref. pt. is top of G <sup>2</sup> guard with lid removed. Contract drilled.	
							Private Water Facility. Normal pump rate 30,000 g.p.h. Seasonal variation N.S. to 35 ft.
BORE No. SITE No.	Commenced Completed	LM50 1965	LM49 1965	B7 S6 26-7-65 9-3-65			
Drilling Time hrs.				34 1/2			
Other Productive Time hrs.				15			
SCREEN SETTINGS				Bore not screened			
PUMP TEST No.		No Test	No Test	No Test			
PUMP TYPE							
SUCTION AT							
DATE				16-3-65	15-12-66		
S.W.L. (below N.S.)				11'-4"	16'-8"		
AVAILABLE D.D.							
DURATION							
FINAL PUMP RATE G.P.H.							
FINAL D.D.							
RECOVERY TIME							
RESIDUAL D.D.							
WATER QUALITY	Location	No Sample	No Sample	2.5 ft.	84 to 90 ft.		
	Conductivity at 25°C			21,000	5,920		
	Total Solids			15,100	3,400		
	Chlorides as Cl <sup>-</sup>			8,900	1,600		
	Alkalinity			116	336		
	Hardness			3,660	530		
	pH			7.2	7.0		
	Date			1-3-65	4-3-65		
REMARKS		Unsuccessful G <sup>2</sup> private test bore.	Unsuccessful 3" private test bore.	Casing removed and pilot pipe inserted. Ref. pt. is top of G <sup>2</sup> guard with lid removed.			



BORE No.	Commenced	BI.	15-7-65	BIA	16-7-65
SITE No.	Completed	SI.	16-7-65	SIA	3-8-65
Drilling Time	hrs.		6½		23½
Other Productive Time	hrs.		4¼		35¼
SCREEN SETTINGS	Bore not Screened		36'-0" Top Packer. 37'-3" Bot Casing. 1x0-050 1x0-060 1x0-073 45'-0" Bot Cap 6" Willscreens.		
PUMP TEST No.	No Test				Pilot Pipe
PUMP TYPE			Pomona		BISI
SUCTION AT			34'-0"		
DATE		16-7-65	15-12-66	23-7-65	23-7-65
S.W.L. (below N.S.)		10'-9"	18'-3"	9'-3"	11'-0"
AVAILABLE D.D.			24'-9"		
DURATION			360 mins.		360 mins.
FINAL PUMP RATE G.P.H.			31,700		
FINAL D.D.			9'-3"		1'-2"
RECOVERY TIME			50 mins.		50 mins.
RESIDUAL D.D.			6½"		5½"
WATER QUALITY	Location	37'-6" to 48'-0"		37'-6" to 45'-0"	
	Conductivity at 25°C	270		252	
	Total Solids	170		151	
	Chlorides as Cl <sup>-</sup>	20		24	
	Alkalinity	108		124	
	Hardness	64		60	
	pH	7.8		7.8	
	Date	23-7-65		23-7-65	
REMARKS	Casing removed and pilot pipe inserted.		8 galls. of sand removed in 4 hours by bailing, shock and solid surging in screens.		
	All bores drilled 8" dia. for full depth.		Casing and screens removed. No pilot pipe inserted.		
BORE No.	Commenced				
SITE No.	Completed				
Drilling Time	hrs.				
Other Productive Time	hrs.				
SCREEN SETTINGS					
PUMP TEST No.					
PUMP TYPE					
SUCTION AT					
DATE					
S.W.L.					
AVAILABLE D.D.					
DURATION					
FINAL PUMP RATE G.P.H.					
FINAL D.D.					
RECOVERY TIME					
RESIDUAL D.D.					
WATER QUALITY	Location				
	Conductivity at 25°C				
	Total Solids				
	Chlorides as Cl <sup>-</sup>				
	Alkalinity				
	Hardness				
	pH				
REMARKS					




**LEGEND**

Aquifer


c.g. Coarse grained  
 s. With

LEVEL BOOK: 14311



QUEENSLAND  
 IRRIGATION AND WATER SUPPLY COMMISSION  
 HAUGHTON RIVER  
 GROUND WATER INVESTIGATION  
 WOODSTOCK ROAD LINE

BORE No.	Commenced	BI.	15-7-65	BIA	16-7-65
SITE No.	Completed	SI.	16-7-65	SIA	3-8-65
Drilling Time	hrs.		6½		23½
Other Productive Time	hrs.		4¼		35¼
SCREEN SETTINGS	Bore not Screened		36'-0" Top Packer. 37'-3" Bot Casing. 1x0-050 1x0-060 1x0-073 45'-0" Bot Cap 6" Willscreens.		
PUMP TEST No.	No Test				Pilot Pipe
PUMP TYPE			Pomona		BISI
SUCTION AT			34'-0"		
DATE		16-7-65	15-12-66	23-7-65	23-7-65
S.W.L. (below N.S.)		10'-9"	18'-3"	9'-3"	11'-0"
AVAILABLE D.D.			24'-9"		
DURATION			360 mins.		360 mins.
FINAL PUMP RATE G.P.H.			31,700		
FINAL D.D.			9'-3"		1'-2"
RECOVERY TIME			50 mins.		50 mins.
RESIDUAL D.D.			6½"		5½"
WATER QUALITY	Location	37'-6" to 48'-0"	37'-6" to 45'-0"		
	Conductivity at 25°C	270	252		
	Total Solids	170	151		
	Chlorides as Cl <sup>-</sup>	20	24		
	Alkalinity	108	124		
	Hardness	64	60		
	pH	7.8	7.8		
	Date	23-7-65	23-7-65		
REMARKS	Casing removed and pilot pipe inserted.		8 galls. of sand removed in 4 hours by bailing, shock and solid surging in screens.		
	All bores drilled 8" dia. for full depth.		Casing and screens removed. No pilot pipe inserted.		
	Ref. pt. is top of 6" guard with lid removed.				




**LEGEND**

Aquifer





c.g. Coarse grained  
 s. With

LEVEL BOOK: 14311



QUEENSLAND  
 IRRIGATION AND WATER SUPPLY COMMISSION  
 HAUGHTON RIVER  
 GROUND WATER INVESTIGATION  
 WOODSTOCK ROAD LINE

BORE No.	Commenced	B3	3-12-65	B3-A	7-12-65	17-1-66	B1	18-11-65	B1-A	23-11-65	B2	1-12-65	
SITE No.	Completed	S1	7-12-65	S1-A	10-12-65	19-1-66	S2	22-11-65	S2-A	30-11-65	S3	2-12-65	
Drilling Time	hrs.	6		3 3/4			7 1/2		4 1/2		3 1/2		
Other Productive Time	hrs.	8		21			4 1/2		3 1/2		4 1/2		
SCREEN SETTINGS	Bore not Screened.	28'-10" Top packer 30'-4" Bot casing. 1x 0-060 32'-9" Bot cap. 6" Williscreeen.		Bore not Screened.		30'-3" Top packer 31'-4 1/2" Bot casing. 1x 0-050 1x 0-060 36'-6" Bot cap. 6" Williscreeen.		Bore not Screened.					
	No Test	Pomona 24'-2"		No Test		Bailer B1S2		No Test					
PUMP TEST No.		7-12-65		15-12-65		18-1-66		22-11-65		15-12-66		30-11-65	
PUMP TYPE		13'-5"		15'-11"		8'-8"		10'-4"		13'-8"		14'-1"	
SUCTION AT		15'-6"								16'-7"		Dry	
DATE		360 mins.		360 mins.				120 mins.		120 mins.			
S.W.L. (below N.S.)		15,900						1,200					
AVAILABLE D.D.		10'-8 3/4"		1'-1"				11'-7"		0"			
DURATION		60 mins.		60 mins.				6 mins.		6 mins.			
FINAL PUMP RATE G.P.H.		0'-6"		0'-4 3/4"				0"		0"			
FINAL D.D.		20'-0" to 33'-8"		30'-4" to 32'-9"		17 ft to 30 ft.		13 ft to 35 ft.					
RECOVERY TIME		820		590		780		515					
RESIDUAL D.D.		492		354		448		309					
WATER QUALITY	Location	20'-0" to 33'-8"		30'-4" to 32'-9"		17 ft to 30 ft.		13 ft to 35 ft.					
in	Conductivity at 25°C	100		68		140		72					
Micromhos per cm	Total Solids	296		216		115		156					
& ppm.	Chlorides as Cl <sup>-</sup>	104		88		190		30					
	Alkalinity	8.1		7.5		7.2		7.5					
	Hardness	7-12-65		18-1-66		19-11-65		30-11-65					
	pH												
	Date												
REMARKS		Casing removed and pilot pipe inserted. Ref. pt. is top of 6" guard with lid removed.		Casing and screens removed. No pilot pipe inserted.		Casing removed and pilot pipe inserted. Ref. pt. is top of 6" guard with lid removed.		91 gallons of sand removed in 13 3/4 hours by bailing, shock, solid and valve surging in screens and casing. Casing and screens removed. No pilot pipe inserted.		Casing removed. No pilot pipe inserted.			
BORE No.	Commenced												
SITE No.	Completed												
Drilling Time	hrs.												
Other Productive Time	hrs.												
SCREEN SETTINGS													
PUMP TEST No.													
PUMP TYPE													
SUCTION AT													
DATE													
S.W.L.													
AVAILABLE D.D.													
DURATION													
FINAL PUMP RATE G.P.H.													
FINAL D.D.													
RECOVERY TIME													
RESIDUAL D.D.													
WATER QUALITY	Location												
in	Conductivity at 25°C												
Micromhos per cm	Total Solids												
& ppm.	Chlorides as Cl <sup>-</sup>												
	Alkalinity												
	Hardness												
	pH												
REMARKS													



LEVELS DATUM : STATE


LEGEND



fg. Fine grained  
c.g. Coarse grained  
c With



LEVEL BOOK : 14306

SCALE



QUEENSLAND  
IRRIGATION AND WATER SUPPLY COMMISSION  
HAUGHTON RIVER  
GROUND WATER INVESTIGATION  
ANABRANCH LINE

BORE No.	Commenced	B1	20-8-64	B6	9-2-65 and 23-3-65	B2	1-9-64		
SITE No.	Completed	S2	31-8-64	S3	26-2-65 and 1-4-65	S4	14-9-64		
Drilling Time	hrs.	32							
Other Productive Time	hrs.	74 1/4							
SCREEN SETTINGS	Bore not screened					Bore not screened			
PUMP TEST No.	No Test	Bailer Test				No Test			
PUMP TYPE									
SUCTION AT									
DATE		31-8-64	15-12-66	31-3-65	15-12-66	23-11-64	14-9-66		
S.W.L. (below N.S.)		4'-8"	8'-11"	3'-1"	7'-11"	4'-11"	5'-6"		
AVAILABLE D.D.		53'-5"							
DURATION		60 mins.							
FINAL PUMP RATE G.P.H.		1,200							
FINAL D.D.		45'-4"							
RECOVERY TIME		30 mins.							
RESIDUAL D.D.		0'-5 1/2"							
WATER QUALITY in Micromhos per cm & ppm.	Location	21'-8"	21'-8"	8'-0"	23'-0"	54 to 62 ft.	68 to 71 ft.	77 to 82 ft.	136'-6"
	Conductivity at 25°C	11,500	4,000	21,000	17,000	6,180	7,300	11,500	33,000
	Total Solids		2,649	15,520	11,200	2,850	4,450	7,420	20,000
	Chlorides as Cl <sup>-</sup>		1,030	8,000	5,800	1,600	2,200	3,800	17,400
	Alkalinity		25	0	0	120	256	256	150
	Hardness		900	3,200	0	400	750	1,310	11,360
pH		6.5	5.1	6.1	7.9	7.1	7.0	7.0	
Date		14-9-66	18-4-67	10-2-65	10-2-65	11-2-65	11-2-65	11-2-65	4-10-66
REMARKS	All bores drilled 8" dia. for full depth.	Casing removed and pilot pipe inserted. Ref. pt. is top of 2" G.I. pipe with cap removed. Contract drilled.	Cement-bentonite seal placed 68 to 75 ft. 27 1/2 gallons of sand removed in 23 1/2 hours by bailing, shock and valve surging in screens and casing. Casing and screens removed and pilot pipe inserted. Ref. pt. is top of 6" guard with lid removed.				Casing removed and pilot pipe inserted. Ref. pt. is top of 2" G.I. pipe with cap removed. Contract drilled.		
BORE No.	Commenced	JW37	JW10						
SITE No.	Completed		1960	1947					
Drilling Time	hrs.								
Other Productive Time	hrs.								
SCREEN SETTINGS	0' N.S.	3 x 6" spears.		6 x 3" spears.					
		17' Gauze.		19' Gauze.					
		23' Gauze.							
PUMP TEST No.	No Test	No Test							
PUMP TYPE									
SUCTION AT									
DATE		1-2-67	1-2-67						
S.W.L.		17'-0"	20'-0"						
AVAILABLE D.D.									
DURATION									
FINAL PUMP RATE G.P.H.									
FINAL D.D.									
RECOVERY TIME									
RESIDUAL D.D.									
WATER QUALITY in Micromhos per cm & ppm.	Location	No sample		No sample					
	Conductivity at 25°C								
	Total Solids								
	Chlorides as Cl <sup>-</sup>								
	Alkalinity								
	Hardness								
pH									
REMARKS	Private Water Facility.	Private Water Facility.							
	Normal pump rate 40,000 g.p.h.	Normal pump rate 40,000 g.p.h.							
	Seasonal variation 6 ft. to 17 ft.	Seasonal variation 5 ft. to 20 ft.							




**LEGEND**

Aquifer

c.g. Coarse grained & With

Natural Surface Levels taken from Main Roads Survey



QUEENSLAND IRRIGATION AND WATER SUPPLY COMMISSION

HAUGHTON RIVER

GROUND WATER INVESTIGATION

**TOWNSVILLE ROAD LINE**

(ANABRANCH SECTION)